

MODELS 600/850

SERIES A-D

SPECIAL APPLICATION AIR DRYER



Features

- Adjustable system pressure allows for altitude compensation to assure peak efficiency at any elevation.
- Compressor isolation provides quiet, vibration free operation and extends service life.
- Large ASME air storage tank reduces cycling for improved component life.
- Forced air ventilation allows cooler operation and improved efficiency.
- Self-regenerating twin tower drying system for years of trouble free operation.

Fully automatic, self-contained compressor dehydrators, Radiodetection's Models 600 and 850 provide a dry air source for a variety of small volume applications. These units are quiet and compact making them the ideal choice for your low volume dry air (less than 2% RH) requirements. The Models 600 and 850 air dryers are available in four alarm / output pressure configurations and in 115V / 60-50Hz to provide optimum capabilities for all applications. With an adjustable outlet pressure of 2 to 15 PSIG. (0.1 to 2.0 PSIG in the "D" series) standard units are available to fit most requirements.

These units are ideally suited for specialty pressurization requirements such as toll cable, repeater site, broad-cast transmission line, waveguide, and CEV (Controlled Environment Vault) pressurization. In addition, these units can be manufactured to either commercial or military specifications for applications in ground based and mobile radar systems.

Models 600 and 850 air dryers feature a reliable twin tower heatless air dryer and a long life compressor well suited for high altitude operation. Cabinet air flow via forced air ventilation as well as sophisticated vibration isolation optimize the service life of these units. In addition, special consideration has been given to accessibility and ease of maintenance to provide a versatile, full featured pressurization package.

600 / 850 OPTION DESIGNATIONS

OPTIONS ARE KEYED TO LAST LETTER OF MODEL DESIGNATION

LETTER

-A The output pressure regulator allows adjustment of the output pressure from 2 to 15 PSIG. This unit comes equipped with a color-change Humidity Indicator, an adjustable Low Output Pressure Alarm, Power Off Alarm, Power On indicator light, and Summary Alarm Terminal Board. Both "Closed in Alarm" and "Open in Alarm" conditions can be monitored from the alarm terminal board.

-B The output pressure regulator allows adjustment of the output pressure from 2 to 15 PSIG. This unit is equipped with an Electronic Humidity Alarm factory preset to alarm at 2% RH (-20° dew point). Other standard features include an adjustable Low Output Pressure Alarm, and Power Off Alarm Power-On Indicator Light and a Summary Alarm Terminal Board. Both "Closed in Alarm" and "Open in Alarm" conditions can be monitored from the alarm terminal board.

-C The output pressure regulator allows adjustment of the output pressure from 2 to 15 PSIG. This unit is equipped with an Electronic Humidity Alarm, factory preset to alarm at 2% RH (-20° dew point), and a humidity Bypass with automatic reset. Other standard features include an adjustable Low Output Pressure Alarm, adjustable High Output Pressure Alarm, Excessive Operation Alarm, and Power Off alarm. Front Panel indicator lights provide confirmation of alarm status and a segregated Alarm Terminal Board provides remote recognition of 5 separate alarm conditions or a single "Summary" alarm condition. Both "Closed in Alarm" and "Open in Alarm" conditions can be monitored from the alarm terminal board.

-D A precision low pressure regulator allows adjustment of the output pressure from 0.1 to 2.0 PSIG. This model is equipped with an Electronic humidity alarm, factory preset to alarm at 2% RH (-20° dew point), and a humidity Bypass with automatic reset. Other standard features include adjustable Low Output and High Output pressure Alarms, Excessive Operation Alarm and Power Off Alarm. Front panel indicator lights provide verification of alarm status and a Segregated Alarm Terminal Board provides remote recognition of five separate alarm conditions or a single "Summary" alarm condition. Both "Closed in Alarm" and "Open in Alarm" conditions can be monitored from the alarm terminal board.

SPECIFICATIONS

CHARACTERISTICS	MODEL 600	MODEL 850
Normal Capacity	600 S.C.F.D.	850 S.C.F.D.
Maximum Capacity	750 S.C.F.D.	1080 S.C.F.D.
Dew Point	-40°F (-40°C)	-40°F (-40°C)
Operating Voltage	115V/60-50Hz, 230V/60-50Hz	115V/60-50Hz, 230V/60-50Hz
Operating Amps	6.0 (115V), 3.0 (230V)	6.5 (115V), 3.2 (230V)
Circuit Protection (manual reset) Compressor	10 Amp (115V), 5 Amp (230V)	10 Amp (115V), 5 Amp (230V)
Width	1/4 H.P.	1/4 H.P.
Height	17.5 Inches	17.5 Inches
Depth	15.5 Inches	15.5 Inches
Weight	17.5 Inches	17.5 Inches
Air Outlet	85 Lbs.	85 Lbs.
	3/8" O.D. Tube Fitting	3/8" O.D. Tube Fitting

Specialists in Cable Pressurization



Global locations

USA

SPX Global Headquarters

13515 Ballantyne Corporate Place
Charlotte, NC 28277, USA
Tel: +1 704 752 4400
www.spx.com

Radiodetection

28 Tower Road, Raymond, Maine 04071, USA
Tel: +1 (207) 655 8525
Toll Free: +1 (877) 247 3797
Fax: +1 (207) 655 8535
rd.sales.us@spx.com
www.radiodetection.com

Pearpoint

39-740 Garand Lane, Unit B
Palm Desert, CA 92211, USA
Tel: +1 800 688 8094
Tel: +1 760 343 7350
Fax: +1 760 343 7351
pearpoint.sales.us@spx.com
www.radiodetection.com

Radiodetection (Canada)

344 Edgeley Boulevard, Unit 34
Concord, Ontario L4K 4B7, Canada
Tel: +1 (905) 660 9995
Toll Free: +1 (800) 665 7953
Fax: +1 (905) 660 9579
rd.sales.ca@spx.com
www.radiodetection.com

EUROPE

Radiodetection Ltd. (UK)

Western Drive, Bristol BS14 0AF, UK
Tel: +44 (0) 117 976 7776
Fax: +44 (0) 117 976 7775
rd.sales.uk@spx.com
www.radiodetection.com

Radiodetection (France)

13 Grande Rue, 76220, Neuf Marché, France
Tel: +33 (0) 2 32 89 93 60
Fax: +33 (0) 2 35 90 95 58
rd.sales.fr@spx.com
<http://fr.radiodetection.com>

Radiodetection (Benelux)

Industriestraat 11
7041 GD 's-Heerenberg, Netherlands
Tel: +31 (0) 314 66 47 00
Fax: +31 (0) 314 66 41 30
rd.sales.nl@spx.com
<http://nl.radiodetection.com>

Radiodetection (Germany)

Groendahlscher Weg 118
46446 Emmerich am Rhein, Germany
Tel: +49 (0) 28 51 92 37 20
Fax: +49 (0) 28 51 92 37 520
rd.sales.de@spx.com
<http://de.radiodetection.com>

ASIA-PACIFIC

Radiodetection (Asia-Pacific)

Room 708, CC Wu Building
302-308 Hennessy Road, Wan Chai
Hong Kong SAR, China
Tel: +852 2110 8160
Fax: +852 2110 9681
rd.sales.cn@spx.com
www.radiodetection.com

Radiodetection (China)

Hongfu Mansion, Room 61622
Zheng Ge Zhuang, Bei Qi Jia Town
Chang Ping District
Beijing 102209, China
Tel: +86 (0) 10 8178 5652
Fax: +86 (0) 10 8178 5662
rd.service.cn@spx.com
<http://cn.radiodetection.com>

Radiodetection (Australia)

Unit H1, 101 Rookwood Road,
Yagoona NSW 2199, Australia
Tel: +61 (0) 2 9707 3222
Fax: +61 (0) 2 9707 3788
rd.sales.au@spx.com
www.radiodetection.com

Radiodetection is a leading global developer and supplier of test equipment used by utility companies to help install, protect and maintain their infrastructure networks. Radiodetection is a unit of SPX (NYSE: SPW), a global Fortune 500 multi-industry manufacturing company. With headquarters in Charlotte, N.C., SPX has 18,000 employees in more than 35 countries worldwide. Visit www.spx.com.

Copyright 2013 Radiodetection Ltd - SPX Corporation. All rights reserved. Radiodetection is a subsidiary of SPX Corporation. SPX, the green ">" and "X" are trademarks of SPX Corporation, Inc. Radiodetection, Dielectric, SmartTech, DRY-PAK are trademarks of Radiodetection Ltd. and SPX Corporation. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Radiodetection Ltd.