

Where Ideas Meet Industry

# Surface and Ambient Sensing Thermostats **VE and C8 Series**



## **VE** Series

**Description:** VE Surface Temperature Sensors are temperature operated switches ideally suited for applications requiring small, precise but rugged devices. They are designed to sense surface temperature within very narrow differentials with a high degree of reliability.

**Operations:** VE Surface Temperature Sensors have a unique dual bimetal design which produces larger forces and contact motion than ordinarily found in devices of this size. Intimate coupling between the mounting base and actuating elements produces an exceptionally fast response time. Contact chatter is eliminated and the unit has no resonant points below 2000 Hz.

## **Advantages**

- Miniature size
- Direct Metallic Heat Conduction
- Rapid Response
- High Shock and Vibration Characteristics
- Field Adjustable
- Hermetically Sealed (optional)

## **Applications**

- Semiconductor Heat Sinks
- Crystal and Capacitor Ovens
- Cooling System Control
- Computer Systems
- Motors and Generators
- Alarm Systems

## **Military Environments**

Designed for military environments for exposure to -55°C to +150°C, the VE Series meets the rugged shock and vibration requirements associated with military and high-grade industrial applications. Typical control applications include:

- Heat Sinked Components
- Electronic Systems
- Temperature Sensitive Systems

- Frequency Stability
- Power Supplies
- Heat Dissipation Systems

- Motors, Generators, Compressors
  Truck, Railcar Environmental Applications

Specifications					
Setting:	See table (page 15). Unit can be set to any temperature within the specified ranges.	Contact:	Open on rise or close on rise Rating: 3A @ 115 VAC Resistive 1A @ 32 VDC		
Setting Tolerance:	<u>+</u> 5°F ( <u>+</u> 3°C)		Resistive		
		Vibration:	10g to 2000Hz. *		
*when temperature is at least	3°C from the actual temperature setting	Shock:	10g 11 msec*		



<u>C8 Series</u>

**Description:** C8 Ambient Temperature Sensors are cartridgesize thermal switches ideally suited to control or monitor temperature in either air or liquid mediums. Available in different mounting arrangement, they provide a high degree of sensitivity and operate under severe environmental conditions.

**Operations:** C8 Sensors are based on a differential expansion principle, comparing the expansion or contraction of the outer shell in relation to an internal member that is not affected by temperature. The differential in expansion of these two members is then multiplied by the internal mechanism and transferred as a motion to the contacts. The contacts are built in a separate fused glass header with a minimum current path to reduce self-heating effects.

## Advantages

- Fast response Time
- Narrow Temperature Differential
- Hermetically Sealed
- Stable Under Severe Shock and Vibration

## Applications

- Heating and Cooling Equipment
- Ventilation Systems
- Fire Detection
- Hydraulic Systems
- Critical Temperature Equipment

## **Military Environments**

Designed for military environments for exposure to -55°C to +150°C, the C8 Series meets the rugged shock and vibration requirements associated with military and high-grade industrial applications. Typical control and alarm applications include:

- Heating and Cooling Equipment
- Ventilation Systems Fire Detection
- Hydraulic Systems
- Critical Temperature Equipment

Specifications				
Setting Tolerance:	± 5°F (±3°C)	Vibration:	25g to 1000Hz.*	
Contact:	S.P.S.T. open on rise or S.P.S.T. close on rise	Shock:	50g 11 msec*	
	5A @ 115 VAC Resistive 1A @ 32 VDC Resistive	Material:	C8-C, C8-B, C8-F Brass zinc plated with chromate finish C8-P is nickel plated	
*when temperature is at least 3°C from the actual temperature setting				

## **SERIES VE**

## **SERIES C8**

- Factory Set and Hermetically Sealed Contact factory. Specify desired temperature setting °F or °C and indicate open on rise or close on rise contact configuration.
- 2) Field Adjustable-Unsealed. Order from table below.

TEMP	MODEL NO.		
RANGE	Contact Open on Rise	Contact Close on Rise	
0°C to +55°C +32°F to +131°F	VE-2101	VE-2102	
+50°C to +105°C +122°F to +221°F	VE-3101	VE-3102	
+100°C to +150°C +212°F to +300°F	VE-4101	VE-4102	
-50°C to +5°C -67°F to +41°F	VE-1101	VE-1102	

#### Mounting:

Model		Type of Mounting		
C8-C	-	No mounting bracket		
C8-B	-	Side mounting bracket		
C8-F		3-hole flange mount		
C8-P	-	Pipe fitting		
Contact:				
0.R.	-	Open on Rise		
C.R.	-	Close on Rise		
E. J. T. T. Station Collins				

#### Factory Temperature Setting:

-25°C to +150°C -30°F to +300°F

#### Example:

To order a 3-hole flange mounted C8 unit set for 80°F with normally closed contacts-

SPECIFY-C8-F, 0.R., 80°F

## **OUTLINE DIMENSIONS**

Detailed outline drawings with tolerances are available on request.

Detailed outline drawings with tolerances are available on request.



062 DIA HOLE 3/16 1/2 MAX. 1/16 MAX.

Direct replacement for Fenwal Series 32410/32411-The Fenwal Company discontinued this popular surface sensing series in 1987-The Warren G-V Series VE Thermostat mounts on the same 1.00" centerline as direct replacement, meeting all electrical and thermal requirements of the former unit.





Radiodetection is a proud member of the SPX group of companies, which provide technical products and service solutions worldwide.

Radiodetection and its associated companies specialize in the design and manufacture of products for the location and maintenance of underground pipes and cables. Our aim is to be viewed as the supplier of choice of 'high performance' quality equipment using advanced product technologies. We are also committed to both design innovation and customer support.

## America

#### Radiodetection

154 Portland Road Bridgton, ME 04009, USA Tel: +1 (207) 647 9495 Toll Free: +1 (877) 247 3797 Fax: +1 (207) 647 9496 Email: rd.sales.us@spx.com Web: www.radiodetection.com

#### Pearpoint

72055 Corporate Way Thousand Palms CA 92276, USA Tel: +1 800 688 8094 Tel: +1 760 343 7350 Fax: +1 760 343 7351 Email: pearpoint.sales.us@spx.com Web: www.radiodetection.com

#### Radiodetection (Canada)

344 Edgeley Boulevard, Unit 34 Concord, Ontario L4K 4B7, Canada Tel: +1 (905) 660 9995 Toll Free: +1 (800) 665 7953 Fax: +1 (905) 660 9579 Email: rd.sales.ca@spx.com Web: www.radiodetection.com

To see the full range of products and services provided by Radiodetection visit: WWW.radiodetection.com

## Technical support



Radiodetection equipment users have easy access to technical support. A call to your regional representative, or the Radiodetection head office, will put you in contact with our team of field-experienced technical experts.



Radiodetection has a team of factory-trained service technicians and dedicated service facilities. Turnaround is fast, and costs are very competitive.

# Training

Product training for your operators and training personnel is available on your site, or at Radiodetection's headquarters. Training is with qualified instructors and each trainee receives a certificate to confirm they have received the training.

## Europe

## Radiodetection Ltd (UK)

Western Drive Bristol BS14 0AF, UK Tel: +44 (0) 117 976 7776 Fax: +44 (0) 117 976 7775 Email: rd.sales.uk@spx.com Web: www.radiodetection.com

#### Radiodetection (France)

13 Grande Rue, 76220 Neuf Marché, France Tel: +33 (0) 232 8993 60 Fax: +33 (0) 235 9095 58 Email: rd.sales.fr@spx.com Web: http://fr.radiodetection.com

#### Radiodetection (Benelux)

Industriestraat 11 7041 GD 's-Heerenberg, Netherlands Tel: +31 (0) 314 66 47 00 Fax: +31 (0) 314 66 41 30 Email: rd.sales.nl@spx.com Web: http://nl.radiodetection.com

#### Radiodetection (Germany)

Groendahlscher Weg 118 46446 Emmerich am Rhein, Germany Tel: +49 (0) 28 51 92 37 20 Fax: +49 (0) 28 51 92 37 520 Email: rd.sales.de@spx.com Web: http://de.radiodetection.com

## Asia-Pacific

#### Radiodetection (Asia-Pacific)

Room 708, CC Wu Building 302-308 Hennessy Road, Wan Chai Hong Kong SAR, China Tel: +852 2110 8160 Fax: +852 2110 9681 Email: rd.sales.cn@spx.com Web: www.radiodetection.com

#### Radiodetection (China)

Hongfu Mansion, Room 61622 Zheng Ge Zhuang, Bei Qi Jia Town Chang Ping District Beijing 102209, China Tel: +86 (0) 10 8975 5540 Fax: +86 (0) 10 8975 5640 Email: rd.service.cn@spx.com Web: http://cn.radiodetection.com

#### Radiodetection (Australia)

Unit 14, 5-7 Prosperity Parade Warriewood NSW 2102, Australia Tel: +61 (0) 2 9979 8555 Fax: +61 (0) 2 9979 7733 Email: rd.sales.au@spx.com Web: www.radiodetection.com



Radiodetection products are under continuous development and are subject to change, we reserve the right to alter or amend any published specification without notice.

Copyright 2008 Radiodetection Ltd. - SPX Corporation. All rights reserved. Radiodetection Ltd. is a subsidiary of SPX Corporation.



Global Headquarters 13515 Ballantyne Corporate Place Charlotte, North Carolina 28277 United States Where Ideas Meet Industry

# Where Ideas Meet Industry

www.spx.com